

2- door working cover style safety cabinet for corrosives

COMPLIANCE

FM - OSHA - NFPA

ADVANTAGES

- NFPA and OSHA compliant
- FM compliant
- Storage of corrosives

BUT ALSO...

- Fixation for earthing
- Continuous piano hinges
- Containment sump integrated with HDPE protection
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height with HDPE protection
- Integrated door handle



TECHNICAL FEATURES

Model	B30M	Door closure	manual closing
Compliance	FM - OSHA - NFPA	Shipping dimensions HxWxD (mm)	1320 x 1200 x 800
Cabinet materials	Double wall steel structure	Ventilation	Both inlet and outlet
Doors color	blue	Openings diameter (mm)	50
Number of doors	2	Number of compartments	1
Doors type	swing doors		88.00
Hinges	right & left	HS Code	2147483647

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Filtration box built in PVC with activated carbon filter for organic and corrosive vapors (Réf : CDF-P)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Shelf for cabinets B30M - B30S (Réf : ESP30)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
B30M	1118 x 1092 x 457	1025 x 1005 x 390	113		1	159	88.00