



INSTRUCTIONS FOR USE
PRODUCT SPECIFIC INFORMATION
ONLY ON THIS PAGE



INSTRUCTIONS FOR USE - CATEGORY II



EN



SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION



DECLARATION OF CONFORMITY



EXPLANATION OF PICTOGRAMS



EN



EN 407:2020



PROTECTIVE GLOVES AGAINST THERMAL RISKS (HEAT AND/OR FIRE)



A: Limited flame spread



Min. 0; Max. 4



B: Contact heat



Min. 0; Max. 4



C: Connective heat



Min. 0; Max. 4



D: Radiant heat



Min. 0; Max. 4



E: Small splashes of molten metal



Min. 0; Max. 4



F: Large quantities of molten metal



Min. 0; Max. 4



A: Abrasion resistance



Min. 0; Max. 4



B: Blade cut resistance



Min. 0; Max. 4



C: Tear resistance



Min. 0; Max. 4



D: Puncture resistance



Min. 0; Max. 4



E: Cut Resistance TDM



Min. 0; Max. 4



F: Impact Protection



P=Pass



A: Abrasion resistance



Min. 0; Max. 4



B: Blade cut resistance



Min. 0; Max. 4



C: Tear resistance



Min. 0; Max. 4



D: Puncture resistance



Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

Min. 0; Max. 4

F: Impact Protection

P=Pass

A: Abrasion resistance

Min. 0; Max. 4

B: Blade cut resistance

Min. 0; Max. 4

C: Tear resistance

Min. 0; Max. 4

D: Puncture resistance

Min. 0; Max. 4

E: Cut Resistance TDM

