



INSTRUCTIONS FOR USE
PRODUCT SPECIFIC INFORMATION
ONLY ON THIS PAGE

TEGERA® 804

Synthetic glove, nitrile, 3/4 dipped, double-dipped, sandy finish, cut resistance level C, carbon, CRF- Technology, glass fibre thread, HPPE, polyester, spandex, Cat. II, black, blue, grey, withstands contact heat up to 100°C, latex-free, for touchscreen, oil and grease resistant, for assembly work

EN ISO 21420:2020



EN 388:2016+A1:2018
3X41C

EN 407:2020 No Flame Protection
X1XXXX

IEC 61340-5-1:2016
R < 1.0 x 10⁹ Ω

EN 16350:2014
R < 1.0 x 10⁹ Ω



dermatec
garantie.de



STANDARD 100
SE 14-214
RISE



Contact heat rating valid for palm area only

OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), polyester, glass fibre thread, elastane, carbon thread

SIZE RANGE (EU) 6,7,8,9,10,11

EU-TYPE EXAMINATION (MODULE B) ISSUED BY NOTIFIED BODY: 2777 Satra Technology Europe Ltd Bractown Business Park, Clonee, Co. Meath, Ireland

EN 407:2020 SKYDDSHANDSKAR MOT TERMISKA RISKEN (HETTA OCH/ELLER BRAND)



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4

6 PAIRS



Min. O. Max. 4




INSTRUCTIONS FOR USE - CATEGORY II
SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION




Carefully read these instructions before using this product.


EXPLANATION OF PICTOGRAMS = O = Below the minimum performance level for the given individual hazard X= Not submitted to the test or test method not suitable for the glove design and material



Min. O. Max. 4



Min. O. Max. 4




Min. O. Max. 4



Min. O. Max. 4

EN ISO 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS

EN 407:2020 SKYDDSHANDSKAR MOT TERMISKA RISKEN (HETTA OCH/ELLER BRAND)



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4




KÄYTTÖOHJEET - KATEGORIA II
KATSO ETUSIVU TUOTEKOHTAISTEN TIETOJEN OSALTA




Lue nämä ohjeet huolellisesti ennen tämän tuotteen käyttöä.

VAATIMUSTENHUKKAUSVAKUUTUS
www.jendals.com/conformity




Min. O. Max. 4



Min. O. Max. 4




Min. O. Max. 4




Min. O. Max. 4

EN ISO 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS

EN 407:2020 SKYDDSHANDSKAR MOT TERMISKA RISKEN (HETTA OCH/ELLER BRAND)



Min. O. Max. 4




Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4




Lisez attentivement ces instructions avant d'utiliser le produit.




Attentionnez ces instructions avant d'utiliser le produit.

EXPLICATION DES PICTOGRAMMES = O = Sous le niveau de performance minimal pour le risque individuel donné X= Non-testés ou méthode d'essai utilisée non adaptée au type de gant/matériau




Min. O. Max. 4



Min. O. Max. 4




Min. O. Max. 4



Min. O. Max. 4

EN ISO 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS


EN 407:2020 SKYDDSHANDSKAR MOT TERMISKA RISKEN (HETTA OCH/ELLER BRAND)




Min. O. Max. 4




Min. O. Max. 4




Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4



Min. O. Max. 4

